

View Online at <https://aerobasegroup.com/nsn/4820-00-777-6752>

Pipe Size Accommodated:

0.125 inches 2nd end

Thread Class:

3a 1st end

Thread Direction:

Right-hand 1st end

Flow Control Device:

Poppet

Bonnet Type:

Inside spring

Bonnet Attachment Method:

Integral

Disk Loading Method:

Spring

Maximum Operating Temp:

180.0 degrees fahrenheit single response

Connection Style:

Plain (pipe) 2nd end

Valve Operation Method:

Automatic

Connection Type:

Threaded external tube 1st end

Features Provided:

Bonnet packing and pressure tight outlet side

Thready Qty Per Inch (tpi):

27 2nd end

Adjustable Pressure Range:

+115.0/+250.0 pounds per square inch

Maximum Operating Pressure:

250.0 pounds per square inch single response

Thread Size:

0.437 inches 1st end

Seat Angle:

37.0 degrees 1st end

Opening Pressure Setting:

200.0 pounds per square inch

Outside Diameter Tube Accommodated:

0.250 inches 1st end

Material:

Stainless steel flow control device and plastic polytetrafluoroethylene flow control device

Material Specification:

Ams 3651 military standard 2nd material response flow control device

Media For Which Designed:

Oil, hydraulic single response

Surface Treatment:

Passivate

Style Designator:

Angle

Thread Series Designator:

Unf 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A046b0