NSN 4820-00-778-4819

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-778-4819

| Flow Control Device: |
|---|
| Disk |
| Bonnet Type: |
| Packing retaining |
| Disk Loading Method: |
| Spring |
| Bolt Hole Quantity: |
| 6 1st end |
| Valve Operation Method: |
| Automatic |
| Flange Shape: |
| Round with holes 1st end |
| Connection Type: |
| Flange 1st end |
| Mounting Facility: |
| Bracket |
| Valve Size: |
| 1.500 inches |
| Outside Diameter: |
| 5.062 inches 1st end |
| Thickness: |
| 0.437 inches 1st end |
| First Connection Face To Centerline Distance: |
| 3.875 inches |
| Bolt Hole Diameter: |
| 0.562 inches 1st end |
| Second Connection Face To Centerline Distance: |
| 3.875 inches |
| Bolt Circle Diameter: |
| 3.937 inches 1st end |
| Flange Face Design: |
| Plain 1st end |
| Material: |
| Copper alloy 606 and copper alloy 614 and copper alloy 630 seat |
| Style Designator: |
| Err-090 |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |

No

NSN 4820-00-778-4819

Safety Relief Valve - Page 2 of 2



Fiig:

A046b0