NSN 4820-00-779-4832

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-779-4832

Thread Direction:
Right-hand all ends
Flow Control Device:
Poppet
Bonnet Type:
Inside spring
Bonnet Attachment Method:
Threaded
Disk Loading Method:
Spring
Maximum Operating Temp:
250.0 degrees fahrenheit single response
Minimum Operating Temp:
-20.0 degrees fahrenheit
Connection Style:
Plain, optional en (pipe) all ends
Valve Operation Method:
Automatic
Connection Type:
Threaded internal pipe all ends
Features Provided:
Valve stem lock shield
Maximum Operating Pressure:
10500.0 pounds per square inch single response
Thread Size:
0.500 inches all ends
Opening Pressure Setting:
500.0 pounds per square inch
Material:
Steel comp 303 body
Material Specification:
Fed standard 66 federal standard single material response body
Media For Which Designed:
Nitrogen, gaseous 5th response
Style Designator:
Straight through note: to be used for valve bodies of one section only.
Thread Series Designator:
Npt all ends
Shelf Life:
N/a
Unit Of Measure:

--

NSN 4820-00-779-4832

Safety Relief Valve - Page 2 of 2



Demilitarization:

No

Fiig:

A046b0