NSN 4820-00-781-6881

Globe Valve - Page 1 of 2

Flow Control Device:



View Online at https://aerobasegroup.com/nsn/4820-00-781-6881

| Disk |
|--|
| Bonnet Type: |
| Outside screw-yoke |
| Bonnet Attachment Method: |
| Bolted |
| Bolt Hole Quantity: |
| 4 1st end |
| Valve Operation Method: |
| Manual |
| Flange Shape: |
| Round with holes 1st end |
| Connection Type: |
| Flange 1st end |
| Features Provided: |
| Bonnet packing |
| Maximum Operating Pressure: |
| 150.0 pounds per square inch single response |
| Outside Diameter: |
| 5.125 inches 1st end |
| Thickness: |
| 1.000 inches 1st end |
| Bolt Hole Diameter: |
| 0.875 inches 1st end |
| Bolt Circle Diameter: |
| 3.500 inches 1st end |
| Flange Face Design: |
| Raised straight 1st end |
| Raised Face Height: |
| 0.250 inches 1st end |
| Raised Face Diameter: |
| 1.688 inches 1st end |
| Material: |
| Steel body |
| Style Designator: |
| Straight thru |
| Reference Number Differentiating Characteristics: |
| Quality controlled in accordance with navy level 1 assurance guide |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |

NSN 4820-00-781-6881

Globe Valve - Page 2 of 2



| em | | | |
|----|--|--|--|
| | | | |
| | | | |

No

Fiig:

A046b0