## NSN 4820-00-781-7154

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-781-7154

Thread Class:						
3a 1st end						
Thread Direction:						
Right-hand 1st end						
Flow Control Device:						
Poppet						
Disk Loading Method:						
Spring						
Maximum Operating Temp:						
212.0 degrees fahrenheit single response						
Connection Style:						
Flared (tube) 1st end						
Valve Operation Method:						
Automatic						
Connection Type:						
Threaded external tube 1st end						
Features Provided:						
Pressure tight outlet side						
Adjustable Pressure Range:						
+38.0/+42.0 pounds per square inch						
Maximum Operating Pressure:						
200.0 pounds per square inch single response						
Thread Size:						
0.437 inches 1st end						
Seat Angle:						
37.0 degrees 1st end						
Opening Pressure Setting:						
37.0 pounds per square inch						
Outside Diameter Tube Accommodated:						
0.250 inches 1st end						
Material:						
Steel comp 303						
Material Specification:						
66 federal standard single material response						
Media For Which Designed:						
Water, fresh single response						
Style Designator:						
Straight through w/baffle						
Thread Series Designator:						
Unf 1st end						
Shelf Life:						
N/a						

## NSN 4820-00-781-7154

Safety Relief Valve - Page 2 of 2



	• •				
In	18	<i>(</i> )+	МЛО	201	ure:

--

Demilitarization:

No

Fiig:

A046b0