NSN 4820-00-781-7154



781-7154

Safety Relief Valve - Page 1 of 2
View Online at https://aerobasegroup.com/nsn/4820-00-7
Thread Class:
3a 1st end
Thread Direction:
Right-hand 1st end
Flow Control Device:
Poppet
Disk Loading Method:
Spring
Maximum Operating Temp:
212.0 degrees fahrenheit single response
Connection Style:
Flared (tube) 1st end
Valve Operation Method:
Automatic
Connection Type:
Threaded external tube 1st end
Features Provided:
Pressure tight outlet side
Adjustable Pressure Range:
+38.0/+42.0 pounds per square inch
Maximum Operating Pressure:
200.0 pounds per square inch single response
Thread Size:
0.437 inches 1st end
Seat Angle:
37.0 degrees 1st end
Opening Pressure Setting:
37.0 pounds per square inch
Outside Diameter Tube Accommodated:
0.250 inches 1st end
Material:
Steel comp 303
Material Specification:
66 federal standard single material response
Media For Which Designed:
Water, fresh single response
Style Designator:
Straight through w/baffle
Thread Series Designator:
Unf 1st end
Shelf Life:
N/a

NSN 4820-00-781-7154

Safety Relief Valve - Page 2 of 2

Unit Of Measure:

Demilitarization:

No

Fiig:

A046b0

