NSN 4820-00-781-7820

Stop-lift-check Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-781-7820

Flow Control Device:	
Disk	
Bonnet Type:	
Outside screw-yoke	
Bonnet Attachment Method:	
Bolted	
Renewable Seat Ring Type:	
Threaded	
Bolt Hole Quantity:	
4 1st end	
Valve Operation Method:	
Manual	
Flange Shape:	
Round with holes 1st end	
Connection Type:	
Flange 1st end	
Mounting Position:	
Vertical	
Features Provided:	
Bonnet packing	
Valve Size:	
1.000 inches	
Outside Diameter:	
4.875 inches 1st end	
Thickness:	
0.688 inches 1st end	
First Connection Face To Centerline Distance:	
4.250 inches	
Bolt Hole Diameter:	
0.750 inches 1st end	
Second Connection Face To Centerline Distance:	
4.250 inches	
Bolt Circle Diameter:	
3.500 inches 1st end	
Flange Face Design:	
Raised straight 1st end	
Raised Face Height:	
0.250 inches 1st end	
Raised Face Diameter:	
2.000 inches 1st end	
Material:	
Steel comp 410 stem	

NSN 4820-00-781-7820

Stop-lift-check Valve - Page 2 of 2

Style Designator:

Angle flanged ends

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A530b0

