

View Online at <https://aerobasegroup.com/nsn/4820-00-793-5836>

Thread Class:

3a 1st end

Thread Direction:

Right-hand 1st end

Disk Loading Method:

Spring

Connection Style:

Flared (tube) 1st end

Valve Operation Method:

Manual

Connection Type:

Threaded external tube 1st end

Features Provided:

Valve stem lock shield and pressure tight outlet side

Thread Qty Per Inch (tpi):

20 1st end

Adjustable Pressure Range:

+1000.0/+1400.0 pounds per square inch

Maximum Operating Pressure:

1400.0 pounds per square inch single response

Thread Size:

0.437 inches 1st end

Seat Angle:

37.0 degrees 1st end

Opening Pressure Setting:

1170.0 pounds per square inch

Outside Diameter Tube Accommodated:

0.250 inches 1st end

Material:

Stainless steel flow control device

Material Specification:

Qq-a-225/6 federal specification single material response body

Media For Which Designed:

Air single response

Surface Treatment:

Anodize

Style Designator:

Straight thru

Test Data Document:

33525-840892 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Thread Series Designator:

Unf 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A046b0