NSN 4820-00-794-1776



Safety Relief Valve - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/4820-00-794-1776 **Thread Class:** 3b 1st end **Thread Direction:** Right-hand 1st end Flow Control Device: **Poppet Bonnet Type:** Inside spring **Bonnet Attachment Method:** Threaded **Disk Loading Method:** Spring **Connection Style:** Gasket sea (boss) all ends **Valve Operation Method:** Automatic **Connection Type:** Threaded internal boss 2nd end **Mounting Facility:** Threaded fastener **Features Provided:** Bonnet packing Thready Qty Per Inch (tpi): 18 2nd end **Adjustable Pressure Range:** +10.0/+200.0 pounds per square inch **Thread Size:** 0.750 inches 1st end **Outside Diameter Tube Accommodated:** 0.500 inches 1st end Material: Aluminum alloy 208.0 body or aluminum alloy 319.0 body or aluminum alloy 328.0 body **Material Specification:** Qq-a-601, t6 federal specification single material response body **Style Designator:** Angle **Thread Series Designator:** Unf 2nd end Shelf Life: N/a

Unit Of Measure:

NSN 4820-00-794-1776

Safety Relief Valve - Page 2 of 2



Demilitarization:

No

Fiig:

A046b0