## NSN 4820-00-794-1776

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-794-1776

Thread Class:

3b 1st end

**Thread Direction:** 

Right-hand 1st end

#### Flow Control Device:

Poppet

#### Bonnet Type:

Inside spring

#### **Bonnet Attachment Method:**

Threaded

#### **Disk Loading Method:**

Spring

#### Connection Style:

Gasket sea (boss) all ends

### Valve Operation Method:

Automatic

### Connection Type:

Threaded internal boss 2nd end

#### Mounting Facility:

Threaded fastener

#### **Features Provided:**

Bonnet packing

#### Thready Qty Per Inch (tpi):

18 2nd end

#### Adjustable Pressure Range:

+10.0/+200.0 pounds per square inch

#### Thread Size:

0.750 inches 1st end

#### **Outside Diameter Tube Accommodated:**

0.500 inches 1st end

#### Material:

Aluminum alloy 208.0 body or aluminum alloy 319.0 body or aluminum alloy 328.0 body

#### Material Specification:

Qq-a-601, t6 federal specification single material response body

#### Style Designator:

Angle

**Thread Series Designator:** 

Unf 2nd end

Shelf Life:

N/a

#### Unit Of Measure:

--

# NSN 4820-00-794-1776

Safety Relief Valve - Page 2 of 2

Demilitarization:

No

Fiig:

A046b0

