NSN 4820-00-794-6283

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-794-6283 **Thread Class:** 3a all ends **Thread Direction:** Right-hand all ends Flow Control Device: **Poppet Disk Loading Method:** Spring **Valve Discharge Flow Rate:** 1.0 gallons per minute **Maximum Operating Temp:** 160.0 degrees fahrenheit single response **Connection Style:** Gasket sea (boss) all ends **Valve Operation Method:** Automatic **Connection Type:** Threaded internal boss all ends **Features Provided:** Pressure tight outlet side **Maximum Operating Pressure:** 3000.0 pounds per square inch single response **Thread Size:** 0.437 inches all ends **Opening Pressure Setting:** 3000.0 pounds per square inch **Outside Diameter Tube Accommodated:** 0.250 inches all ends Material: Iron cast Media For Which Designed: Fuel/oil, hydrocarbon single response **Style Designator:** Err-090 **Thread Series Designator:** Unf all ends Shelf Life: N/a **Unit Of Measure:**

Demilitarization:

Yes - demil/mli

NSN 4820-00-794-6283

Safety Relief Valve - Page 2 of 2



Fiig:

A046b0

Mil-std (military Standard):

Mil-v-8566 spec.