

View Online at <https://aerobasegroup.com/nsn/4820-00-795-5476>

Thread Class:

3a 1st end

Thread Direction:

Right-hand 1st end

Flow Control Device:

Piston

Disk Loading Method:

Spring

Renewable Seat Ring Type:

Pressed-in

Maximum Operating Temp:

160.0 degrees fahrenheit single response

Connection Style:

Flared (tube) 1st end

Valve Operation Method:

Air

Connection Type:

Threaded external tube 1st end

Thready Qty Per Inch (tpi):

20 1st end

Power Drive Operating Pressure:

3000.0 pounds per square inch

Thread Size:

0.437 inches 1st end

Seat Angle:

37.0 degrees 1st end

Outside Diameter Tube Accommodated:

0.250 inches 1st end

Surface Treatment:

Anodize

Surface Treatment Specification:

Mil-a-8625 military specification single treatment response

Style Designator:

Straight thru

Test Data Document:

81349-mil-e-5272 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Unf 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A046b0

Mil-std (military Standard):

Mil-a-8625 spec.