NSN 4820-00-800-1562

Check Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-800-1562 **Thread Class:** 3a 1st end **Thread Direction:** Right-hand all ends Flow Control Device: Poppet **Disk Loading Method:** Spring **Maximum Operating Temp:** 200.0 degrees fahrenheit single response **Connection Style:** Plain, optional end (pipe) 2nd end **Valve Operation Method:** Automatic **Connection Type:** Threaded internal pipe 2nd end **Mounting Position:** Horizontal or vertical Thready Qty Per Inch (tpi): 12 1st end **Maximum Operating Pressure:** 3000.0 pounds per square inch single response **Thread Size:** 1.625 inches 1st end Seat Angle: 37.0 degrees 1st end Material: Stainless steel flow control device and rubber butadiene-acrylonitrile class nbr flow control device **Material Specification:** Fed standard 66, aisi 303/sae 30303 federal standard single material response seat Media For Which Designed: Hydraulic fluid, silicate-ester base 4th response **Surface Treatment: Passivate Style Designator:** Straight thru **Thread Series Designator:** Un 1st end Shelf Life: N/a

Unit Of Measure:

NSN 4820-00-800-1562

Check Valve - Page 2 of 2



Demilitarization:

No

Fiig:

A530b0