NSN 4820-00-800-6156

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-800-6156

| Pipe Size Accommodated: |
|---------------------------|
| 0.750 inches 1st end |
| Thread Direction: |
| Right-hand 1st end |
| Flow Control Device: |
| Poppet |
| Bonnet Type: |
| Inside spring |
| Bonnet Attachment Method: |

Threaded

Disk Loading Method:

Spring

Valve Discharge Flow Rate:

15.0 cubic feet per minute

Maximum Operating Temp:

170.0 degrees fahrenheit 2nd response

Connection Style:

Plain, optional en (pipe) 1st end

Valve Operation Method:

Automatic or manual

Connection Type:

Threaded internal pipe 1st end

Features Provided:

Valve stem lock shield and bonnet packing and pressure tight outlet side

Thready Qty Per Inch (tpi):

14 2nd end

Maximum Operating Pressure:

300.0 pounds per square inch 2nd response

Thread Size:

0.750 inches 1st end

Opening Pressure Setting:

10.0 pounds per square inch

Material:

Steel stem

Style Designator:

Angle

Thread Series Designator:

Npt 1st end

Reference Number Differentiating Characteristics:

As differentiated by valve size andset pressure

Shelf Life:

N/a

NSN 4820-00-800-6156

Safety Relief Valve - Page 2 of 2

Unit Of Measure:

Demilitarization:

No

Fiig:

A046b0

