NSN 4820-00-800-6156

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-800-6156

Pipe Size Accommodated:
0.750 inches 1st end
Thread Direction:
Right-hand 1st end
Flow Control Device:
Poppet
Bonnet Type:
Inside spring
Bonnet Attachment Method:
Threaded
Disk Loading Method:
Spring
Valve Discharge Flow Rate:
15.0 cubic feet per minute
Maximum Operating Temp:
170.0 degrees fahrenheit 2nd response
Connection Style:
Plain, optional en (pipe) 1st end
Valve Operation Method:
Automatic or manual
Connection Type:
Threaded internal pipe 1st end
Features Provided:
Valve stem lock shield and bonnet packing and pressure tight outlet side
Thready Qty Per Inch (tpi):
14 2nd end
Maximum Operating Pressure:
300.0 pounds per square inch 2nd response
Thread Size:
0.750 inches 1st end
Opening Pressure Setting:
10.0 pounds per square inch
Material:
Steel stem
Style Designator:
Angle
Thread Series Designator:
Npt 1st end
Reference Number Differentiating Characteristics:
As differentiated by valve size andset pressure
Shelf Life:
N/a

NSN 4820-00-800-6156

Safety Relief Valve - Page 2 of 2



		• •			
ш	ın	10	<i>(</i>)+	Measure:	

--

Demilitarization:

No

Fiig:

A046b0