NSN 4820-00-802-2225

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-802-2225

Thread Class:
3a 1st end
Thread Direction:
Right-hand 1st end
Flow Control Device:
Poppet
Disk Loading Method:
Spring
Maximum Operating Temp:
-40.0 degrees fahrenheit 1st response270.0 degrees fahrenheit 2nd response
Connection Style:
Flared (tube) 1st end
Valve Operation Method:
Automatic
Connection Type:
Threaded external tube 1st end
Features Provided:
Pressure tight outlet side
Adjustable Pressure Range:
+0.0/+200.0 pounds per square inch
Maximum Operating Pressure:
200.0 pounds per square inch single response
Thread Size:
0.437 inches 1st end
Seat Angle:
37.0 degrees 1st end
Opening Pressure Setting:
15.0 pounds per square inch
Outside Diameter Tube Accommodated:
0.250 inches 1st end
Material:
Steel comp 303 stem
Material Specification:
Fed standard 66 federal standard single material response stem
Media For Which Designed:
Hydrogen 5th response
Style Designator:
Straight through note: to be used for valve bodies of one section only.
Thread Series Designator:
Unjf 1st end
Shelf Life:
N/a

NSN 4820-00-802-2225

Safety Relief Valve - Page 2 of 2



		eas	

--

Demilitarization:

No

Fiig:

A046b0