NSN 4820-00-803-7495

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-803-7495

Thread Class:
3b 1st end
Thread Direction:
Right-hand 1st end
Flow Control Device:
Poppet
Bonnet Type:
Packing retaining
Disk Loading Method:
Spring
Valve Discharge Flow Rate:
6.0 gallons per minute
Maximum Operating Temp:
160.0 degrees fahrenheit single response
Connection Style:
Gasket sea (boss) 1st end
Valve Operation Method:
Automatic
Connection Type:
Threaded internal boss 1st end
Thready Qty Per Inch (tpi):
18 1st end
Maximum Operating Pressure:
1500.0 pounds per square inch single response
Thread Size:
0.562 inches 1st end
Opening Pressure Setting:
1750.0 pounds per square inch
Outside Diameter Tube Accommodated:
0.375 inches 1st end
Material:
Steel comp 440c seat
Media For Which Designed:
Hydraulic fluid, phosphate-ester base single response
Style Designator:
Straight thru
Thread Series Designator:
Unf 1st end
Shelf Life:
N/a
Unit Of Measure:

--

NSN 4820-00-803-7495

Safety Relief Valve - Page 2 of 2



Demilitarization:

No

Fiig:

A046b0