## NSN 4820-00-808-6681

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-808-6681

Thread Class:
3a 1st end
Thread Direction:
Right-hand 1st end
Flow Control Device:
Poppet
Bonnet Type:
Packing retaining
Disk Loading Method:
Spring
Maximum Operating Temp:
212.0 degrees fahrenheit single response
Connection Style:
G42 flared (tube) 1st end
Valve Operation Method:
Automatic
Connection Type:
Threaded external tube 1st end
Features Provided:
Pressure tight outlet side
Thready Qty Per Inch (tpi):
18 1st end
Thread Size:
0.562 inches 1st end
Seat Angle:
37.0 degrees 1st end
Opening Pressure Setting:
4.0 pounds per square inch
Outside Diameter Tube Accommodated:
0.375 inches 1st end
Special Features:
Valve anodized medium gray
Material:
Rubber synthetic packing
Material Specification:
Qq-a-225/6 federal specification single material response body
Media For Which Designed:
Oil 2nd response
Surface Treatment:
Anodize
Surface Treatment Specification:
Mil-a-8625, type 1 military specification single treatment response

## NSN 4820-00-808-6681

Safety Relief Valve - Page 2 of 2

Style Designator:

Err-090

Thread Series Designator:

Unf 1st end

Furnished Items And Quantity:

1 gasket

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A046b0

Mil-std (military Standard):

Mil-a-8625 spec.

