## NSN 4820-00-809-8915

Safety Relief Valve - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/4820-00-809-8915

Thread Direction: Right-hand 1st end Flow Control Device: Disk Disk Loading Method: Spring Maximum Operating Temp: 406.0 degrees fahrenheit single response Connection Style: G9 plain, optional en (pipe) 2nd end Valve Operation Method: Automatic or manual Connection Type: Threaded internal pipe 2nd end Features Provided: Valve stem lock shield Adjustable Pressure Range: + 145.0/+158.0 pounds per square inch Maximum Operating Pressure: 300.0 pounds per square inch single response Thread Size: 1.500 inches 2nd end Special Features: 3rd media for pressure is gas Material: Steel stem Media For Which Designed: Fuel/oil, hydrocarbon 3rd response Style Designator: Err-090 Thread Series Designator: Npt 1st end Reference Number Differentiating Characteristics: Aifferentiated by relief pressure setting, valve size, and material Shell Life: N/a Unit of Measure:  Demilitarization: No Fig: A046b0	
Fow Control Device:DiskDisk Loading Method:SpringMaximum Operating Temp:406.0 degrees fahrenheit single responseConnection Style:G9 plain, optional en (pipe) 2nd endValve Operation Method:Automatic or manualConnection Type:Threaded internal pipe 2nd endFeatures Provided:Valve stem lock shieldAdjustable Pressure Range:+145.0/+158.0 pounds per square inchMaximum Operating Pressure:300.0 pounds per square inch single responseThread Size:1.500 inches 2nd endSpecial Features:3rd media for pressure is gasMaterial:Steel stemMedia For Which Designed:Fuel/oil, hydrocarbon 3rd responseStyle Designator:Fur-090Thread Series Designator:As differentiated by relief pressure setting, valve size, and materialSheft Life:N/aUnit of Measure:NaFuel/oil, hydrocarbon SupponseSheft Life:N/aParameter Differentiating Characteristics:As differentiated by relief pressure setting, valve size, and materialSheft Life:N/aUnit of Measure:NoFig:	Thread Direction:
Disk Disk Loading Method: Spring Maximum Operating Temp: 406.0 degrees fahrenheit single response Connection Style: G9 plain, optional en (pipe) 2nd end Valve Operation Method: Automatic or manual Connection Type: Threaded internal pipe 2nd end Features Provided: Valve stem lock shield Adjustable Pressure Range: +145.0/+158.0 pounds per square inch Maximum Operating Pressure: 300.0 pounds per square inch single response Thread Size: 1.500 inches 2nd end Special Features: 3rd media for pressure is gas Material: Steel stem Media For Which Designed: Fuel/oil, hydrocarbon 3rd response Style Designator: Fuel/oil, hydrocarbon 3rd response Style Designator: Npt 1st end Reference Number Differentiating Characteristics: As differentiated by relief pressure setting, valve size, and material Shell Life: N/a Uni Of Measure: Tomilitarization: No Fig:	Right-hand 1st end
Disk Loading Method:         Spring         Maximum Operating Temp:         406.0 degrees fahrenheit single response         Connection Style:         G9 plain, optional en (pipe) 2nd end         Valve Operation Method:         Automatic or manual         Connection Type:         Threaded internal pipe 2nd end         Features Provided:         Valve stem lock shield         Adjustable Pressure Range:         +145.0/+158.0 pounds per square inch         Maximum Operating Pressure:         300.0 pounds per square inch single response         Thread Size:         1.500 inches 2nd end         Special Features:         3rd media for pressure is gas         Material:         Steel stem         Media For Which Designed:         Fue/oil, hydrocarbon 3rd response         Style Designator:         Err-090         Thread Series Designator:         Npt 1st end         Reference Number Differentiating Characteristics:         Na         Uit of Measure:         ·         Demilitarization:         No         Fig:	Flow Control Device:
Spring         Maximum Operating Temp:         406.0 degrees fahrenheit single response         Connection Style:         G9 plain, optional en (pipe) 2nd end         Valve Operation Method:         Automatic or manual         Connection Type:         Threaded internal pipe 2nd end         Features Provided:         Valve stem lock shield         Adjustable Pressure Range:         +145.0/+158.0 pounds per square inch         Maximum Operating Pressure:         300.0 pounds per square inch single response         Thread Size:         1.500 inches 2nd end         Special Features:         3rd media for pressure is gas         Material:         Steel stem         Media For Which Designed:         Fue/oil, hydrocarbon 3rd response         Style Designator:         Fur-090         Thread Series Designator:         Npt 1st end         Reference Number Differentiating Characteristics:         Na         Unit Of Measure:            Demilitarization:         No         Fing:	Disk
Maximum Operating Temp:         406.0 degrees fahrenheit single response         Connection Style:         G9 plain, optional en (pipe) 2nd end         Valve Operation Method:         Automatic or manual         Connection Type:         Threaded internal pipe 2nd end         Features Provided:         Valve stem lock shield         Adjustable Pressure Range:         +145.0/+158.0 pounds per square inch         Maximum Operating Pressure:         300.0 pounds per square inch single response         Thread Size:         1.500 inches 2nd end         Special Features:         3rd media for pressure is gas         Material:         Steel stem         Media For Which Designed:         Fur-090         Thread Series Designator:         Npt 1st end         Reference Number Differentiating Characteristics:         As differentiated by relief pressure setting, valve size, and material         Shelf Life:         N/a         Unit Of Measure:            Demilitarization:         No         Fig:	Disk Loading Method:
406.0 degrees fahrenheit single response Connection Style: G9 plain, optional en (pipe) 2nd end Valve Operation Method: Automatic or manual Connection Type: Threaded internal pipe 2nd end Features Provided: Valve stem lock shield Adjustable Pressure Range: +145.0/+158.0 pounds per square inch Maximum Operating Pressure: 300.0 pounds per square inch single response Thread Size: 1.500 inches 2nd end Special Features: 3rd media for pressure is gas Material: Steel stem Media For Which Designed: Fuel/oil, hydrocarbon 3rd response Style Designator: Fur-090 Thread Series Designator: Apt 1st end Reference Number Differentiating Characteristics: As differentiated by relief pressure setting, valve size, and material Shelf Life: N/a Unit Of Measure:  Demilitarization: No	Spring
Connection Style: G9 plain, optional en (pipe) 2nd end Valve Operation Method: Automatic or manual Connection Type: Threaded internal pipe 2nd end Features Provided: Valve stem lock shield Adjustable Pressure Range: +145.0/+158.0 pounds per square inch Maximum Operating Pressure: 300.0 pounds per square inch single response Thread Size: 1.500 inches 2nd end Special Features: 3rd media for pressure is gas Material: Steel stem Media For Which Designed: Fuel/oil, hydrocarbon 3rd response Style Designator: Fur-090 Thread Series Designator: Npt 1st end Reference Number Differentiating Characteristics: As differentiated by relief pressure setting, valve size, and material Sheff Life: N/a Unit Of Measure:  Demilitarization: No	Maximum Operating Temp:
G9 plain, optional en (pipe) 2nd end Valve Operation Method: Automatic or manual Connection Type: Threaded internal pipe 2nd end Features Provided: Valve stem lock shield Adjustable Pressure Range: +145.0/+158.0 pounds per square inch Maximum Operating Pressure: 300.0 pounds per square inch single response Thread Size: 1.500 inches 2nd end Special Features: 3rd media for pressure is gas Material: Steel stem Media For Which Designed: Fuel/oil, hydrocarbon 3rd response Style Designator: Furead Series Designator: Npt 1st end Reference Number Differentiating Characteristics: As differentiated by relief pressure setting, valve size, and material Shelf Life: N/a Unit Of Measure:  Demilitarization: No	406.0 degrees fahrenheit single response
Valve Operation Method: Automatic or manual Connection Type: Threaded internal pipe 2nd end Features Provided: Valve stem lock shield Adjustable Pressure Range: +145.0/+158.0 pounds per square inch Maximum Operating Pressure: 300.0 pounds per square inch single response Thread Size: 1.500 inches 2nd end Special Features: 3rd media for pressure is gas Material: Steel stem Media For Which Designed: Fuel/oil, hydrocarbon 3rd response Style Designator: Fur-090 Thread Series Designator: Npt 1st end Reference Number Differentiating Characteristics: As differentiated by relief pressure setting, valve size, and material Shelf Life: N/a Unit Of Measure:  Demilitarization: No	Connection Style:
Automatic or manualConnection Type:Threaded internal pipe 2nd endFeatures Provided:Valve stem lock shieldAdjustable Pressure Range:+145.0/+158.0 pounds per square inchMaximum Operating Pressure:300.0 pounds per square inch single responseThread Size:1.500 inches 2nd endSpecial Features:3rd media for pressure is gasMaterial:Steel stemMedia For Which Designed:Fue/Joil, hydrocarbon 3rd responseStyle Designator:Fur-090Thread Series Designator:Npt 1st endShelf Life:N/aUnit Of Measure:-Demilitarization:NoFig:	G9 plain, optional en (pipe) 2nd end
Connection Type: Threaded internal pipe 2nd end Features Provided: Valve stem lock shield Adjustable Pressure Range: +145.0/+158.0 pounds per square inch Maximum Operating Pressure: 300.0 pounds per square inch single response Thread Size: 1.500 inches 2nd end Special Features: 3rd media for pressure is gas Material: Steel stem Media For Which Designed: Fuel/oil, hydrocarbon 3rd response Style Designator: Fur-090 Thread Series Designator: Npt 1st end Reference Number Differentiating Characteristics: As differentiated by relief pressure setting, valve size, and material Shelf Life: N/a Unit Of Measure:  Demilitarization: No	Valve Operation Method:
Threaded internal pipe 2nd end Features Provided: Valve stem lock shield Adjustable Pressure Range: +145.0/+158.0 pounds per square inch Maximum Operating Pressure: 300.0 pounds per square inch single response Thread Size: 1.500 inches 2nd end Special Features: 3rd media for pressure is gas Material: Steel stem Media For Which Designed: Fuel/oil, hydrocarbon 3rd response Style Designator: Frr-090 Thread Series Designator: Npt 1st end Reference Number Differentiating Characteristics: As differentiated by relief pressure setting, valve size, and material Shelf Life: N/a Unit Of Measure:  Demilitarization: No	Automatic or manual
Features Provided:Valve stem lock shieldAdjustable Pressure Range:+145.0/+158.0 pounds per square inchMaximum Operating Pressure:300.0 pounds per square inch single responseThread Size:1.500 inches 2nd endSpecial Features:3rd media for pressure is gasMaterial:Steel stemMedia For Which Designed:Fuel/oil, hydrocarbon 3rd responseStyle Designator:Npt 1st endReference Number Differentiating Characteristics:As differentiated by relief pressure setting, valve size, and materialShelf Life:N/aUnit Of Measure:NoFiig:	Connection Type:
Valve stem lock shield Adjustable Pressure Range: +145.0/+158.0 pounds per square inch Maximum Operating Pressure: 300.0 pounds per square inch single response Thread Size: 1.500 inches 2nd end Special Features: 3rd media for pressure is gas Material: Steel stem Media For Which Designed: Fuel/oil, hydrocarbon 3rd response Style Designator: Err-090 Thread Series Designator: Npt 1st end Reference Number Differentiating Characteristics: As differentiated by relief pressure setting, valve size, and material Shelf Life: N/a Unit Of Measure:  Demilitarization: No	Threaded internal pipe 2nd end
Adjustable Pressure Range: +145.0/+158.0 pounds per square inch Maximum Operating Pressure: 300.0 pounds per square inch single response Thread Size: 1.500 inches 2nd end Special Features: 3rd media for pressure is gas Material: Steel stem Media For Which Designed: Fuel/oil, hydrocarbon 3rd response Style Designator: Fur-090 Thread Series Designator: Npt 1st end Reference Number Differentiating Characteristics: As differentiated by relief pressure setting, valve size, and material Shelf Life: N/a Unit Of Measure:  Demilitarization: No	Features Provided:
+145.0/+158.0 pounds per square inch Maximum Operating Pressure: 300.0 pounds per square inch single response Thread Size: 1.500 inches 2nd end Special Features: 3rd media for pressure is gas Material: Steel stem Media For Which Designed: Fuel/oil, hydrocarbon 3rd response Style Designator: Fur-090 Thread Series Designator: Npt 1st end Reference Number Differentiating Characteristics: As differentiated by relief pressure setting, valve size, and material Shelf Life: N/a Unit Of Measure:  Demilitarization: No	Valve stem lock shield
Maximum Operating Pressure:300.0 pounds per square inch single responseThread Size:1.500 inches 2nd endSpecial Features:3rd media for pressure is gasMaterial:Steel stemMedia For Which Designed:Fuel/oil, hydrocarbon 3rd responseStyle Designator:Err-090Thread Series Designator:Npt 1st endReference Number Differentiating Characteristics:As differentiated by relief pressure setting, valve size, and materialShelf Life:N/aUnit Of Measure:Demilitarization:NoFiig:	Adjustable Pressure Range:
300.0 pounds per square inch single response Thread Size: 1.500 inches 2nd end Special Features: 3rd media for pressure is gas Material: Steel stem Media For Which Designed: Fuel/oil, hydrocarbon 3rd response Style Designator: Fur-090 Thread Series Designator: Npt 1st end Reference Number Differentiating Characteristics: As differentiated by relief pressure setting, valve size, and material Shelf Life: N/a Unit Of Measure:  Demilitarization: No	+145.0/+158.0 pounds per square inch
Thread Size: 1.500 inches 2nd end Special Features: 3rd media for pressure is gas Material: Steel stem Media For Which Designed: Fuel/oil, hydrocarbon 3rd response Style Designator: Fur-090 Thread Series Designator: Npt 1st end Reference Number Differentiating Characteristics: As differentiated by relief pressure setting, valve size, and material Shelf Life: N/a Unit Of Measure:  Demilitarization: No	Maximum Operating Pressure:
<ul> <li>1.500 inches 2nd end</li> <li>Special Features:</li> <li>3rd media for pressure is gas</li> <li>Material:</li> <li>Steel stem</li> <li>Media For Which Designed:</li> <li>Fuel/oil, hydrocarbon 3rd response</li> <li>Style Designator:</li> <li>Err-090</li> <li>Thread Series Designator:</li> <li>Npt 1st end</li> <li>Reference Number Differentiating Characteristics:</li> <li>As differentiated by relief pressure setting, valve size, and material</li> <li>Shelf Life:</li> <li>N/a</li> <li>Unit Of Measure:</li> <li></li> <li>Demilitarization:</li> <li>No</li> <li>Fiig:</li> </ul>	300.0 pounds per square inch single response
Special Features: 3rd media for pressure is gas Material: Steel stem Media For Which Designed: Fuel/oil, hydrocarbon 3rd response Style Designator: Err-090 Thread Series Designator: Npt 1st end Reference Number Differentiating Characteristics: As differentiated by relief pressure setting, valve size, and material Shelf Life: N/a Unit Of Measure:  Demilitarization: No Fig:	Thread Size:
Ard media for pressure is gas Material: Steel stem Media For Which Designed: Fuel/oil, hydrocarbon 3rd response Style Designator: Frr-090 Thread Series Designator: Npt 1st end Reference Number Differentiating Characteristics: As differentiated by relief pressure setting, valve size, and material Shelf Life: N/a Dinit Of Measure:  Demilitarization: No Fig:	1.500 inches 2nd end
Material:Steel stemMedia For Which Designed:Fuel/oil, hydrocarbon 3rd responseStyle Designator:Err-090Thread Series Designator:Npt 1st endReference Number Differentiating Characteristics:As differentiated by relief pressure setting, valve size, and materialShelf Life:N/aUnit Of Measure:NoFiig:	Special Features:
Steel stem Media For Which Designed: Fuel/oil, hydrocarbon 3rd response Style Designator: Err-090 Thread Series Designator: Npt 1st end Reference Number Differentiating Characteristics: As differentiated by relief pressure setting, valve size, and material Shelf Life: N/a Unit Of Measure:  Demilitarization: No Fiig:	3rd media for pressure is gas
Media For Which Designed: Fuel/oil, hydrocarbon 3rd response Style Designator: Err-090 Thread Series Designator: Npt 1st end Reference Number Differentiating Characteristics: As differentiated by relief pressure setting, valve size, and material Shelf Life: N/a Unit Of Measure:  Demilitarization: No Fiig:	Material:
Fuel/oil, hydrocarbon 3rd response Style Designator: Err-090 Thread Series Designator: Npt 1st end Reference Number Differentiating Characteristics: As differentiated by relief pressure setting, valve size, and material Shelf Life: N/a Unit Of Measure:  Demilitarization: No Fiig:	Steel stem
Style Designator:   Err-090   Thread Series Designator:   Npt 1st end   Reference Number Differentiating Characteristics:   As differentiated by relief pressure setting, valve size, and material   Shelf Life:   N/a   Unit Of Measure:     Demilitarization:   No   Fiig:	Media For Which Designed:
Err-090 Thread Series Designator: Npt 1st end Reference Number Differentiating Characteristics: As differentiated by relief pressure setting, valve size, and material Shelf Life: N/a Unit Of Measure:  Demilitarization: No Fiig:	Fuel/oil, hydrocarbon 3rd response
Thread Series Designator: Npt 1st end Reference Number Differentiating Characteristics: As differentiated by relief pressure setting, valve size, and material Shelf Life: N/a Unit Of Measure:  Demilitarization: No Fiig:	Style Designator:
Npt 1st end Reference Number Differentiating Characteristics: As differentiated by relief pressure setting, valve size, and material Shelf Life: N/a Unit Of Measure:  Demilitarization: No Fiig:	Err-090
Reference Number Differentiating Characteristics: As differentiated by relief pressure setting, valve size, and material Shelf Life: N/a Unit Of Measure:  Demilitarization: No Fiig:	Thread Series Designator:
As differentiated by relief pressure setting, valve size, and material Shelf Life: N/a Unit Of Measure:  Demilitarization: No Fiig:	Npt 1st end
Shelf Life: N/a Unit Of Measure:  Demilitarization: No Fiig:	Reference Number Differentiating Characteristics:
N/a Unit Of Measure:  Demilitarization: No Fiig:	As differentiated by relief pressure setting, valve size, and material
Unit Of Measure:  Demilitarization: No Fiig:	Shelf Life:
 Demilitarization: No Fiig:	N/a
No Fiig:	Unit Of Measure:
No Fiig:	
Fiig:	Demilitarization:
-	No
A046b0	Fiig:
	A046b0