NSN 4820-00-809-8916

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-809-8916

Pipe Size Accommodated:
0.750 inches 2nd end
Thread Direction:
Right-hand 1st end
Flow Control Device:
Poppet
Bonnet Type:
Inside spring
Bonnet Attachment Method:
Threaded
Disk Loading Method:
Spring
Maximum Operating Temp:
350.0 degrees fahrenheit single response
Connection Style:
G9 plain, optional en (pipe) 1st end
Valve Operation Method:
Automatic
Connection Type:
Threaded internal pipe 1st end
Features Provided:
Valve stem lock shield
Thready Qty Per Inch (tpi):
14 2nd end
Adjustable Pressure Range:
+31.0/+75.0 pounds per square inch
Maximum Operating Pressure:
125.0 pounds per square inch single response
Thread Size:
0.750 inches 2nd end
Material:
Steel stem
Material Specification:
Qq-c-390 federal specification single material response seat
Media For Which Designed:
Steam single response
Style Designator:
Err-090
Thread Series Designator:
Npt 1st end
Shelf Life:

N/a

NSN 4820-00-809-8916

Safety Relief Valve - Page 2 of 2



		• •			
ш	ın	10	<i>(</i>)+	Measure:	

--

Demilitarization:

No

Fiig:

A046b0