NSN 4820-00-810-0569

Stop-lift-check Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-810-0569

Flow Control Device:
Disk
Bonnet Type:
Outside screw-yoke
Bonnet Attachment Method:
Bolted
Bolt Hole Quantity:
4 all ends
Maximum Operating Temp:
850.0 degrees fahrenheit single response
Valve Operation Method:
Manual
Flange Shape:
Round with holes all ends
Connection Type:
Flange all ends
Mounting Position:
Horizontal
Features Provided:
Bonnet packing
Valve Size:
0.500 inches
Maximum Operating Pressure:
600.0 pounds per square inch single response
Outside Diameter:
3.750 inches all ends
Face To Face Distance:
6.500 inches
Thickness:
0.562 inches all ends
Bolt Hole Diameter:
0.562 inches all ends
Bolt Circle Diameter:
2.625 inches all ends
Flange Face Design:
Raised straight all ends
Raised Face Height:
0.250 inches all ends
Raised Face Diameter:
1.375 inches all ends
Material:
Stainless steel stem

NSN 4820-00-810-0569

Stop-lift-check Valve - Page 2 of 2



VI	edia	For	Whic	h Des	sian	ed:
w	cuia		***	11 Des	JIMII	Ju.

Steam single response

Style Designator:

Angle flanged ends

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A530b0