NSN 4820-00-811-2684

Safety Relief Valve - Page 1 of 2

Flow Control Device:

Disk



View Online at https://aerobasegroup.com/nsn/4820-00-811-2684

Bonnet Type:
Inside spring
Bonnet Attachment Method:
Bolted
Disk Loading Method:
Spring
Bolt Hole Quantity:
8 2nd end
Valve Operation Method:
Automatic
Flange Shape:
Round with holes 2nd end
Connection Type:
Flange 1st end
Features Provided:
Valve stem lock shield and bonnet packing
Valve Size:
2.500 inches
Opening Pressure Setting:
120.0 pounds per square inch
Outside Diameter:
7.500 inches 1st end
Thickness:
0.812 inches 2nd end
First Connection Face To Centerline Distance:
5.190 inches
Bolt Hole Diameter:
0.750 inches 2nd end
Second Connection Face To Centerline Distance:
6.500 inches
Bolt Circle Diameter:
6.000 inches 1st end
Flange Face Design:
Raised straight 2nd end
Raised Face Height:
0.062 inches 2nd end
Raised Face Diameter:
5.000 inches 1st end
Material:
Steel

NSN 4820-00-811-2684

Safety Relief Valve - Page 2 of 2



Style Designator:
Err-090
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:

No

Fiig:

A046b0