NSN 4820-00-811-4870

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-811-4870

·····
Thread Class:
3a all ends
Thread Direction:
Right-hand all ends
Flow Control Device:
Poppet
Disk Loading Method:
Spring
Maximum Operating Temp:
275.0 degrees fahrenheit single response
Connection Style:
G45 flareless (tube) all ends
Valve Operation Method:
Automatic
Connection Type:
Threaded external tube all ends
Features Provided:
Pressure tight outlet side
Maximum Operating Pressure:
2400.0 pounds per square inch single response
Thread Size:
0.562 inches all ends
Seat Angle:
12.0 degrees all ends
Opening Pressure Setting:
21.0 pounds per square inch
Outside Diameter Tube Accommodated:
0.375 inches all ends
Material:
Aluminum alloy 2024 body
Material Specification:
Qq-a-225/6, alloy2024 federal specification single material response seat
Media For Which Designed:
Nitrogen, liquid 3rd response
Surface Treatment:
Anodize
Style Designator:
Err-090
Thread Series Designator:
Unjf all ends
Shelf Life:
N/a

NSN 4820-00-811-4870

Safety Relief Valve - Page 2 of 2

Unit Of Measure:

Demilitarization:

No

Fiig:

A046b0

