NSN 4820-00-813-5513

Gate Valve - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/4820-00-813-5513

| Pipe Size Accommodated: |
|--|
| 1.500 inches |
| Bonnet Type: |
| Inside screw |
| Bonnet Attachment Method: |
| Threaded |
| Valve Operation Method: |
| Manual |
| Connection Type: |
| Socket, weld, pipe |
| Features Provided: |
| Bonnet packing |
| Valve Size: |
| 1.500 inches |
| Maximum Operating Pressure And Media For Which Designed: |
| 75.0 pounds per square inch steam and 175.0 pounds per square inch water-oil-gas |
| Stem Type: |
| Nonrising |
| Maximum Operating Tempurature And Media For Which Designed: |
| 250.0 degrees fahrenheit steam and 100.0 degrees fahrenheit water-oil-gas |
| Inlet Relationship With Outlet: |
| Identical |
| Pressure Class: |
| 125.0 pounds |
| Material: |
| Copper alloy 836 disk |
| Material Specification: |
| Astm b-62 assn standard single material response disk |
| Specification Data: |
| 59646-mss sp-80 manufacturers standard |
| Specification Or Standard: |
| A type |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A500a0 |