## NSN 4820-00-813-7032

Check Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-813-7032

## Thread Direction:

Right-hand all ends

**Flow Control Device:** 

Poppet

## **Disk Loading Method:**

Spring

## Maximum Operating Temp:

300.0 degrees fahrenheit single response

#### **Connection Style:**

Plain, optional end (pipe) all ends

## Valve Operation Method:

Automatic

#### Connection Type:

Threaded internal pipe all ends

#### **Mounting Position:**

Horizontal or vertical

#### Maximum Operating Pressure:

3000.0 pounds per square inch single response

#### Thread Size:

0.250 inches all ends

#### **Opening Pressure Setting:**

0.5 pounds per square inch

#### Material:

Stainless steel flow control device

#### **Material Specification:**

Fed-std-66, aisi b1113, 1213/sae 1113 federal standard single material response

#### Media For Which Designed:

Fuel/oil, hydrocarbon 1st response

#### Surface Treatment:

Cadmium

#### Style Designator:

Straight thru

#### **Thread Series Designator:**

Npt all ends

#### Specification Data:

59646-mss-sp-80 manufacturers standard

## **Specification Or Standard:**

125psi class and a end and 0.250 size

#### Shelf Life:

N/a

#### Unit Of Measure:

--

# NSN 4820-00-813-7032

Check Valve - Page 2 of 2

Demilitarization:

No

Fiig:

A530b0

