## NSN 4820-00-814-1858

Safety Relief Valve - Page 1 of 2

Pipe Size Accommodated:



View Online at https://aerobasegroup.com/nsn/4820-00-814-1858

0.500 inches all ends
Thread Direction:
Right-hand all ends
Flow Control Device:
Disk
Bonnet Type:
Inside spring
<b>Bonnet Attachment Method:</b>
Threaded
Disk Loading Method:
Spring
Valve Discharge Flow Rate:
35.9 gallons per minute
Maximum Operating Temp:
406.0 degrees fahrenheit single response
Connection Style:
G9 plain, optional en (pipe) all ends
Valve Operation Method:
Automatic
Connection Type:
Threaded internal pipe all ends
Features Provided:
Pressure tight outlet side
<b>Maximum Operating Pressure:</b>
300.0 pounds per square inch single response
Thread Size:
0.500 inches all ends
Opening Pressure Setting:
200.0 pounds per square inch
Material:
Copper alloy
Media For Which Designed:
Oil 2nd response
Style Designator:
Err-090
Thread Series Designator:
Npt all ends
Shelf Life:
N/a
Unit Of Measure:

--

## NSN 4820-00-814-1858

Safety Relief Valve - Page 2 of 2



Demilitarization:

No

Fiig:

A046b0