## NSN 4820-00-814-2330

Angle Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-814-2330

| Thread Class:                                  |  |  |  |  |  |
|--|--|--|--|--|--|
| 3b all ends                                    |  |  |  |  |  |
| Thread Direction:                              |  |  |  |  |  |
| Right-hand all ends                            |  |  |  |  |  |
| Flow Control Device:                           |  |  |  |  |  |
| Needle   |  |  |  |  |  |
| Bonnet Type:                                   |  |  |  |  |  |
| Inside screw                                   |  |  |  |  |  |
| Bonnet Attachment Method:                      |  |  |  |  |  |
| Threaded                                       |  |  |  |  |  |
| Maximum Operating Temp:                        |  |  |  |  |  |
| 500.0 degrees fahrenheit single response       |  |  |  |  |  |
| Connection Style:                              |  |  |  |  |  |
| G4 gasket sea (boss) all ends                  |  |  |  |  |  |
| Valve Operation Method:                        |  |  |  |  |  |
| Manual   |  |  |  |  |  |
| Connection Type:                               |  |  |  |  |  |
| Threaded internal boss all ends                |  |  |  |  |  |
| Mounting Facility:                             |  |  |  |  |  |
| Bulkhead                                       |  |  |  |  |  |
| Features Provided:                             |  |  |  |  |  |
| Bonnet packing                                 |  |  |  |  |  |
| Maximum Operating Pressure:                    |  |  |  |  |  |
| 10000.0 pounds per square inch single response |  |  |  |  |  |
| Thread Size:                                   |  |  |  |  |  |
| 0.437 inches all ends                          |  |  |  |  |  |
| Outside Diameter Tube Accommodated:            |  |  |  |  |  |
| 0.250 inches all ends                          |  |  |  |  |  |
| Material:                                      |  |  |  |  |  |
| Steel comp 416                                 |  |  |  |  |  |
| Material Specification:                        |  |  |  |  |  |
| Aisi 416 assn standard all material responses  |  |  |  |  |  |
| Media For Which Designed:                      |  |  |  |  |  |
| Water-oil-gas single response                  |  |  |  |  |  |
| Surface Treatment:                             |  |  |  |  |  |
| Passivate                                      |  |  |  |  |  |
| Style Designator:                              |  |  |  |  |  |
| Err-090  |  |  |  |  |  |
| Thread Series Designator:                      |  |  |  |  |  |
| Unf all ends                                   |  |  |  |  |  |
| Shelf Life:                                    |  |  |  |  |  |
|  |  |  |  |  |  |

## NSN 4820-00-814-2330

Angle Valve - Page 2 of 2



|    | • - |      |         |   |
|----|-----|------|---------|---|
| In | ıŧ  | ( )t | Measure | • |
|    |     |      |         |   |

--

Demilitarization:

No

Fiig:

A046b0