## NSN 4820-00-814-4716

Check Valve - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/4820-00-814-4716

| Pipe Size Accommodated:  |
|--|
| 0.750 inches all ends  |
| Thread Direction:  |
| Right-hand all ends  |
| Flow Control Device:   |
| Poppet   |
| Disk Loading Method:   |
| Spring   |
| Maximum Operating Temp:  |
| 200.0 degrees fahrenheit single response                                 |
| Connection Style:  |
| Plain (pipe) all ends  |
| Valve Operation Method:  |
| Automatic  |
| Connection Type:   |
| Threaded external pipe all ends  |
| Mounting Position:   |
| Horizontal or vertical   |
| Thready Qty Per Inch (tpi):  |
| 14 all ends  |
| Maximum Operating Pressure:  |
| 3000.0 pounds per square inch single response                            |
| Thread Size:   |
| 0.750 inches all ends  |
| Material:  |
| Steel comp 304 flow control device or steel comp 303 flow control device |
| Material Specification:  |
| 66 federal standard all material responses flow control device           |
| Media For Which Designed:  |
| Oil single response  |
| Style Designator:  |
| Straight thru  |
| Thread Series Designator:  |
| Npt all ends   |
| Shelf Life:  |
| N/a  |
| Unit Of Measure:   |
|  |
| Demilitarization:  |
| No   |
| Fiig:  |

A530b0