NSN 4820-00-814-6672

Check Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-814-6672

Thread Class:
3a 1st end
Thread Direction:
Right-hand 1st end
Flow Control Device:
Poppet
Disk Loading Method:
Spring
Maximum Operating Temp:
275.0 degrees fahrenheit single response
Connection Style:
Flared (tube) 2nd end
Valve Operation Method:
Automatic
Connection Type:
Threaded external tube 2nd end
Mounting Position:
Horizontal or vertical
Thready Qty Per Inch (tpi):
24 2nd end
Maximum Operating Pressure:
3000.0 pounds per square inch single response
Thread Size:
0.437 inches 1st end
Seat Angle:
37.0 degrees 2nd end
Outside Diameter Tube Accommodated:
0.250 inches 1st end
Material:
Steel comp 440c seat
Material Specification:
Ed-std-66, aisi 440c/sae 51440c federal standard 5th material response seat
Media For Which Designed:
Fuel/oil, hydrocarbon single response
Surface Treatment:
Passivate
Style Designator:
Straight thru
Thread Series Designator:
Unf 2nd end
Shelf Life:
N/a

NSN 4820-00-814-6672

Check Valve - Page 2 of 2



	Of			

--

Demilitarization:

No

Fiig:

A530b0