

View Online at <https://aerobasegroup.com/nsn/4820-00-815-5881>

Thread Class:

3a 1st end

Thread Direction:

Right-hand 1st end

Flow Control Device:

Poppet

Disk Loading Method:

Spring

Maximum Operating Temp:

85.0 degrees fahrenheit single response

Connection Style:

G46a plain (tube) 1st end

Valve Operation Method:

Automatic

Connection Type:

Threaded external tube 1st end

Maximum Operating Pressure:

60.0 pounds per square inch single response

Thread Size:

0.562 inches 1st end

Outside Diameter Tube Accommodated:

0.375 inches 1st end

Material:

Aluminum alloy

Media For Which Designed:

Air single response

Surface Treatment:

Anodize

Surface Treatment Specification:

Mil-a-8625, type 1, class 1 military specification single treatment response

Style Designator:

Err-090

Test Data Document:

18876-10065573 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Thread Series Designator:

Unf 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A046b0

Mil-std (military Standard):

Mil-a-8625 spec.