## NSN 4820-00-816-1476

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-816-1476

| Thread Class:                       |
|-------------------------------------|
| 3a all ends                         |
| Thread Direction:                   |
| Right-hand all ends                 |
| Flow Control Device:                |
| Poppet                              |
| Bonnet Type:                        |
| Packing retaining                   |
| Disk Loading Method:                |
| Spring                              |
| Valve Discharge Flow Rate:          |
| 3.0 gallons per minute              |
| End Application:                    |
| Grumman; a10 aircraft               |
| Connection Style:                   |
| G42 flared (tube) all ends          |
| Valve Operation Method:             |
| Automatic                           |
| Connection Type:                    |
| Threaded external tube all ends     |
| Features Provided:                  |
| Pressure tight outlet side          |
| Thready Qty Per Inch (tpi):         |
| 18 all ends                         |
| Thread Size:                        |
| 0.562 inches all ends               |
| Seat Angle:                         |
| 37.0 degrees all ends               |
| Opening Pressure Setting:           |
| 150.0 pounds per square inch        |
| Outside Diameter Tube Accommodated: |
| 0.375 inches all ends               |
| Material:                           |
| Steel                               |
| Style Designator:                   |
| Err-090                             |
| Thread Series Designator:           |
| Unf all ends                        |
| Shelf Life:                         |
| N/a                                 |
| Unit Of Measure:                    |
|                                     |

## NSN 4820-00-816-1476

Safety Relief Valve - Page 2 of 2



Demilitarization:

No

Fiig:

A046b0