

View Online at <https://aerobasegroup.com/nsn/4820-00-816-4488>

**Thread Class:**

3a 1st end

**Thread Direction:**

Right-hand 1st end

**Flow Control Device:**

Poppet

**Disk Loading Method:**

Spring

**Valve Discharge Flow Rate:**

9.0 pounds per hour

**Connection Style:**

G42 flared (tube) 1st end

**Valve Operation Method:**

Automatic

**Connection Type:**

Threaded external tube 1st end

**Features Provided:**

Valve stem lock shield

**Thready Qty Per Inch (tpi):**

20 1st end

**Adjustable Pressure Range:**

+3250.0/+3500.0 pounds per square inch

**Maximum Operating Pressure:**

3500.0 pounds per square inch single response

**Thread Size:**

0.437 inches 1st end

**Seat Angle:**

37.0 degrees 1st end

**Opening Pressure Setting:**

3500.0 pounds per square inch

**Outside Diameter Tube Accommodated:**

0.250 inches 1st end

**Material:**

Stainless steel flow control device

**Media For Which Designed:**

Air single response

**Surface Treatment:**

Anodize

**Style Designator:**

Err-090

**Supplementary Features:**

Used on all f-4 aircraft

**Test Data Document:**

76050-mc1603 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

**Thread Series Designator:**

Unf 1st end

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fig:**

A046b0