## NSN 4820-00-816-9678

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-816-9678

Thread Class:
3b 1st end
Thread Direction:
Right-hand 1st end
Flow Control Device:
Poppet
Disk Loading Method:
Spring
Valve Discharge Flow Rate:
1.0 gallons per minute
Renewable Seat Ring Type:
Pressed-in
Connection Style:
G9 plain, optional en (pipe) 1st end
Valve Operation Method:
Automatic
Connection Type:
Threaded internal tube 1st end
Features Provided:
Pressure tight outlet side
Thready Qty Per Inch (tpi):
20 1st end
Maximum Operating Pressure:
3000.0 pounds per square inch single response
Thread Size:
0.437 inches 1st end
Outside Diameter Tube Accommodated:
0.250 inches 1st end
Material:
Steel flow control device
Media For Which Designed:
Fuel/oil, hydrocarbon single response
Surface Treatment:
Anodize
Style Designator:
Err-090
Thread Series Designator:
Unjf 1st end
Shelf Life:
N/a
Unit Of Measure:

---

## NSN 4820-00-816-9678

Safety Relief Valve - Page 2 of 2

Demilitarization:

No

Fiig:

A046b0

