

View Online at <https://aerobasegroup.com/nsn/4820-00-819-1044>

Thread Class:

3b 2nd end

Thread Direction:

Right-hand 3rd end

Flow Control Device:

Piston

Valve Discharge Flow Rate:

3.5 gallons per minute

Connection Style:

G42 flared (tube) 3rd end

Connection Type:

Threaded internal tube 1st end

Mounting Facility:

Threaded fastener

Thready Qty Per Inch (tpi):

24 2nd end

Maximum Operating Pressure:

3000.0 pounds per square inch single response

Thread Size:

0.562 inches 3rd end

Seat Angle:

45.0 degrees 3rd end

Outside Diameter Tube Accommodated:

0.375 inches 3rd end

Material:

Rubber synthetic packing

Media For Which Designed:

Hydraulic fluid, phosphate-ester base single response

Surface Treatment:

Anodize

Style Designator:

Err-090

Test Data Document:

81349-mil-v-5530 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Unf 3rd end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A046b0