## NSN 4820-00-820-7659

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-820-7659 **Thread Class:** 3a 1st end **Thread Direction:** Right-hand 1st end Flow Control Device: **Poppet Disk Loading Method:** Spring **Valve Discharge Flow Rate:** 6.0 cubic feet per minute **Maximum Operating Temp:** -100.0 degrees fahrenheit 1st response400.0 degrees fahrenheit 2nd response **Connection Style:** G42 flared (tube) 1st end **Valve Operation Method:** Automatic **Connection Type:** Threaded external tube 1st end **Features Provided:** Pressure tight outlet side **Maximum Operating Pressure:** 200.0 pounds per square inch single response **Thread Size:** 0.437 inches 1st end Seat Angle: 37.0 degrees 1st end **Opening Pressure Setting:** 20.0 pounds per square inch **Outside Diameter Tube Accommodated:** 0.250 inches 1st end Material: Aluminum alloy 2024 body Media For Which Designed: Oxygen, gaseous 3rd response **Style Designator:** Err-090 **Thread Series Designator:** Unjf all ends Shelf Life: N/a

**Unit Of Measure:** 

## NSN 4820-00-820-7659

Safety Relief Valve - Page 2 of 2



Demilitarization:

No

Fiig:

A046b0