## 266



<b>NSN 4820-00-824-1266</b> Restrictor Check Valve - Page 1 of 2
View Online at https://aerobasegroup.com/nsn/4820-00-824-1266
Thread Class:
3a all ends
Thread Direction:
Right-hand all ends
Flow Control Device:
Poppet
Disk Loading Method:
Spring
Maximum Operating Temp:
275.0 degrees fahrenheit single response
Connection Style:
Flareless all ends
Valve Operation Method:
Automatic
Connection Type:
Threaded external tube all ends
Mounting Position:
Horizontal or vertical
Maximum Operating Pressure:
3000.0 pounds per square inch single response
Thread Size:
0.437 inches all ends
Seat Angle:
12.0 degrees all ends
Outside Diameter Tube Accommodated:
0.250 inches all ends
Material:
Steel flow control device
Material Specification:
Qq-a-225/6, alloy 2024 federal specification single material response body
Media For Which Designed:
Hydraulic fluid, phosphate-ester base single response
Surface Treatment:
Anodize

Anodize

#### Surface Treatment Specification:

Mil-a-8625, type 2 military specification single treatment response

#### Style Designator:

Straight thru

### **Thread Series Designator:**

Unf all ends

## Shelf Life:

N/a

# NSN 4820-00-824-1266

Restrictor Check Valve - Page 2 of 2

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A530b0

Mil-std (military Standard):

Mil-a-8625 spec.

