## NSN 4820-00-824-1269

Restrictor Check Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-824-1269 **Thread Class:** 3a all ends **Thread Direction:** Right-hand all ends Flow Control Device: Poppet **Disk Loading Method:** Spring **Maximum Operating Temp:** 275.0 degrees fahrenheit 2nd response **Connection Style:** Flareless all ends **Valve Operation Method:** Automatic **Connection Type:** Threaded external tube all ends **Mounting Position:** Horizontal or vertical **Maximum Operating Pressure:** 3000.0 pounds per square inch single response **Thread Size:** 0.437 inches all ends Seat Angle: 12.0 degrees all ends Material: Steel comp 303 flow control device **Material Specification:** Qq-s-764, type303-canceled federal specification single material response flow control device Media For Which Designed: Hydraulic fluid, petroleum base single response **Surface Treatment:** Enamel **Style Designator:** Straight thru **Test Data Document:** 80378-205-15-2048 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) **Thread Series Designator:** Unjf all ends

--

N/a

Shelf Life:

**Unit Of Measure:** 

## NSN 4820-00-824-1269

Restrictor Check Valve - Page 2 of 2



Demilitarization:

No

Fiig:

A530b0