

View Online at <https://aerobasegroup.com/nsn/4820-00-824-1271>

Thread Class:

3a all ends

Thread Direction:

Right-hand all ends

Flow Control Device:

Poppet

Disk Loading Method:

Spring

Maximum Operating Temp:

275.0 degrees fahrenheit single response

Connection Style:

Flareless all ends

Valve Operation Method:

Automatic

Connection Type:

Threaded external tube all ends

Mounting Position:

Horizontal or vertical

Thready Qty Per Inch (tpi):

20 1st end

Maximum Operating Pressure:

3000.0 pounds per square inch single response

Thread Size:

0.437 inches all ends

Seat Angle:

12.0 degrees all ends

Outside Diameter Tube Accommodated:

0.250 inches all ends

Material:

Stainless steel flow control device and steel comp 303 flow control device and steel comp 304 flow control device

Material Specification:

Qq-a-225/6, alloy 2024 federal specification single material response body

Media For Which Designed:

Hydraulic fluid, phosphate-ester base single response

Surface Treatment:

Anodize

Surface Treatment Specification:

Mil-a-8625, type 2 military specification single treatment response

Style Designator:

Straight thru

Thread Series Designator:

Unf all ends

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A530b0

Mil-std (military Standard):

Mil-a-8625 spec.