NSN 4820-00-824-8648

Globe Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-824-8648

Pipe Size Accommodated:
0.250 inches all ends
Flow Control Device:
Disk
Bonnet Type:
Outside screw-yoke
Bonnet Attachment Method:
Bolted
Maximum Operating Temp:
975.0 degrees fahrenheit single response
Connection Style:
Socket all ends
Valve Operation Method:
Manual
Connection Type:
Unthreaded internal pipe all ends
Features Provided:
Bonnet packing
Maximum Operating Pressure:
1500.0 pounds per square inch single response
Special Features:
Valve size 0.250 in.
Material:
Steel comp 410 stem
Material Specification:
A182, grade f11 assn standard single material response body
Media For Which Designed:
Steam single response
Style Designator:
Err-090
Test Data Document:
31349-mil-v-22094 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Specification Or Standard:
3 composition and 1500 rating
Reference Number Differentiating Characteristics:
As differentiated by style of valve, valve size, pressure rating, and type of end connections
Shelf Life:
N/a
Unit Of Measure:
-

Yes - demil/mli

Demilitarization:

NSN 4820-00-824-8648

Globe Valve - Page 2 of 2



Fiig:

A046b0