
## NSN 4820-00-824-8649

Globe Valve - Page 1 of 2





### Pipe Size Accommodated:

0.375 inches all ends

### **Flow Control Device:**

Disk

## Bonnet Type:

Outside screw-yoke

#### **Bonnet Attachment Method:**

Bolted

#### Maximum Operating Temp:

975.0 degrees fahrenheit single response

#### **Connection Style:**

Socket all ends

#### Valve Operation Method:

Manual

#### **Connection Type:**

Unthreaded internal pipe all ends

Features Provided:

Bonnet packing

## Maximum Operating Pressure:

1500.0 pounds per square inch single response

#### **Special Features:**

Valve size 0.375 in.

#### Material:

Steel body

## **Material Specification:**

A182, grade f11 assn standard single material response body

## Media For Which Designed:

Steam single response

#### Style Designator:

Err-090

## **Test Data Document:**

81349-mil-v-22094 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

## **Specification Or Standard:**

B composition

## **Reference Number Differentiating Characteristics:**

As differentiated by style of valve, valve size, pressure rating, and type of end connections

#### Shelf Life:

N/a

Unit Of Measure:

- --
- Demilitarization:

No

# NSN 4820-00-824-8649

Globe Valve - Page 2 of 2

**Fiig:** A046b0

