NSN 4820-00-824-8652

Globe Valve - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/4820-00-824-8652

| Pipe Size Accommodated: |
|--|
| 1.000 inches all ends |
| Flow Control Device: |
| Disk |
| Bonnet Type: |
| Outside screw-yoke |
| Bonnet Attachment Method: |
| Bolted |
| Maximum Operating Temp: |
| 975.0 degrees fahrenheit single response |
| Connection Style: |
| Socket all ends |
| Valve Operation Method: |
| Manual |
| Connection Type: |
| Unthreaded internal pipe all ends |
| Features Provided: |
| Bonnet packing |
| Maximum Operating Pressure: |
| 1500.0 pounds per square inch single response |
| Special Features: |
| Valve size 1.000 in. |
| Material: |
| Steel comp 410 stem |
| Material Specification: |
| A217, grade wc9 assn standard single material response body |
| Media For Which Designed: |
| Steam single response |
| Style Designator: |
| Err-090 |
| Test Data Document: |
| 81349-mil-v-22094 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification |
| format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain |
| environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A046b0 |