## NSN 4820-00-824-9740

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-824-9740

Pipe Size Accommodated:
0.250 inches 1st end
Thread Direction:
Right-hand 1st end
Flow Control Device:
Poppet
Disk Loading Method:
Spring
Renewable Seat Ring Type:
Retaining screw
Connection Style:
G46b plain (pipe) 1st end
Valve Operation Method:
Automatic
Connection Type:
Threaded external pipe 1st end
Features Provided:
Valve stem lock shield
Thready Qty Per Inch (tpi):
18 1st end
Power Drive Operating Pressure:
7.0 pounds per square inch
Thread Size:
0.250 inches 1st end
Opening Pressure Setting:
7.0 pounds per square inch
Material:
Rubber synthetic seat
Material Specification:
Qq-b-626, comp aa, 1/2h federal specification single material response body
Style Designator:
Err-090
Test Data Document:
18876-9199041 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.;
excludes any specification, standard or other document that may be referenced in a basic governing drawing)
Thread Series Designator:
Npt 1st end
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

No

## NSN 4820-00-824-9740

Safety Relief Valve - Page 2 of 2



Fiig:

A046b0