Globe Valve - Page 1 of 1



Pipe Size Accommodated: 0.500 inches 1st end Flow Control Device: Disk **Bonnet Type:** Outside screw-yoke **Bonnet Attachment Method:** Bolted **Connection Style:** Socket 1st end Valve Operation Method: Manual **Connection Type:** Unthreaded internal pipe 1st end **Maximum Operating Pressure:** 1500.0 pounds per square inch single response

Criticality Code Justification:

Zzzx

Material:

Steel comp xm-10 flow control device or steel comp xm-11 flow control device or steel comp xm-21 flow control device or steel comp xm-26 flow control device or steel comp xm-27 flow control device or steel comp 302 flow control device or steel comp 302 flow control device or steel comp 304 flow control device or steel comp 304 flow control device or steel comp 304 flow control device or steel comp 308 flow control device or steel comp 309 flow control device or steel comp 309 flow control device or steel comp 310 flow control device or steel comp 316 flow control device or steel comp 321 flow control device or steel comp 348 flow control device or steel comp 403 flow control device or steel comp 405 flow control device or steel comp 430 flow control device or steel comp 420 flow control device or steel comp 430 flow control device or steel comp 440 flow co

Err-090

Departure From Cited Designator:

Quality control iaw navships 0948-045-7010 material identification and control instruction for level 1 items

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

Yes - demil/mli

Fiig:

A046b0

