

View Online at <https://aerobasegroup.com/nsn/4820-00-825-2869>

Thread Class:

3a 1st end

Thread Direction:

Right-hand 1st end

Flow Control Device:

Poppet

Connection Style:

Flared (tube) 1st end

Valve Operation Method:

Manual

Connection Type:

Threaded external tube 2nd end

Thready Qty Per Inch (tpi):

12 2nd end

Maximum Operating Pressure:

60.0 pounds per square inch 1st response

Thread Size:

1.312 inches 2nd end

Seat Angle:

37.0 degrees 1st end

Outside Diameter Tube Accommodated:

1.000 inches 2nd end

Media For Which Designed:

Fuel/oil, hydrocarbon single response

Surface Treatment Specification:

Mil-a-8625, type 1 military specification single treatment response

Style Designator:

Straight thru

Test Data Document:

81349-mil-v-25023 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Un 2nd end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A530c0

Mil-std (military Standard):

Mil-a-8625 spec.