## NSN 4820-00-825-8895

Gate Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-825-8895
Pipe Size Accommodated:
3.000 inches
Bonnet Type:
Outside screw-yoke
Bonnet Attachment Method:
Pressure seal, ring type
Valve Operation Method:
Manual
Connection Type:
Butt weld pipe
Features Provided:
Bonnet packing
Valve Size:
3.000 inches
Maximum Operating Pressure And Media For Which Designed:
1500.0 pounds per square inch water-oil-gas
Stem Type:
Rising
Maximum Operating Tempurature And Media For Which Designed:
975.0 degrees fahrenheit water-oil-gas
Inlet Relationship With Outlet:
Identical
Special Features:
50 percent lower operating torque achieved with non-rotating stem and seat wedge flexibility
Material:
Steel seat
Material Specification:
Mil-r-17131 military specification single material response seat
Test Data Document:
81349-mil-s-901 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format
excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental
and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Furnished Items And Quantity:
1 by-pass
Specification Or Standard:
B composition
Departure From Cited Document:
As modified by valve size
Shelf Life:
N/a
Unit Of Measure:
<del></del>

No

Demilitarization:

## NSN 4820-00-825-8895

Gate Valve - Page 2 of 2



Fiig:

A500a0

Mil-std (military Standard):

Mil-r-17131 spec.