

View Online at <https://aerobasegroup.com/nsn/4820-00-828-9925>

**Body Material:**

Steel

**First End Flange Outside Diameter:**

4.625 inches

**Outside Surface Treatment:**

Any acceptable

**Body Style:**

Straight thru

**Furnished Items:**

Internal pilot valve

**Media For Which Designed:**

Steam

**First End Connection Type:**

Raised face flange

**First End Style Designator:**

Raised

**First End Raised Face Height:**

0.250 inches

**First End Raised Face Diameter:**

1.688 inches

**First End Flange Shape Style:**

Round w/ bolt holes

**First End Flange Thickness:**

0.625 inches

**First End Bolt Hole Quantity:**

4

**First End Bolt Hole Diameter:**

0.750 inches

**First End Bolt Circle Diameter:**

3.250 inches

**Second End Relationship With First End:**

Identical

**Seat Material:**

Cobalt alloy

**Face To Face Distance:**

8.500 inches

**Flow Control Device:**

Disk, bevel seat, top and bottom guided

**Flow Control Device Material:**

Steel, corrosion resisting

**End Connection Quantity:**

2

**Outlet Pressure Range:**

+100.0/+450.0 pounds per square inch

**Regulation Type:**

Manual single stage

**Manual Control Method:**

Screw

**Valve Stem Design:**

Single seat

**Valve Loading Method:**

Spring

**Remote Actuation Method:**

Piston

**Maximum Inlet Pressure Rating:**

600.0 pounds per square inch

**Outlet Pressure Accuracy Rating:**

Not rated

**Filter:**

Not included

**Temperature Rating:**

775.0 degrees fahrenheit

**Special Features:**

2630.0 lb per hr at lowest reduced pressure, and 2530.0 lb per hr at highest reduced pressure, flow capacity

**Specification Or Standard:**

A class and d composition and pressure rating 600

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A21100