NSN 4820-00-832-9646

Lift-check Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-832-9646 **Thread Class:** 3a all ends **Thread Direction:** Right-hand all ends Flow Control Device: **Poppet Bonnet Type:** Packing retaining **Disk Loading Method:** Spring **Renewable Seat Ring Type: Bolted Maximum Operating Temp:** 160.0 degrees fahrenheit single response **Connection Style:** Flared (tube) all ends **Valve Operation Method:** Automatic or manual **Connection Type:** Threaded external tube all ends **Mounting Position:** Horizontal or vertical Thready Qty Per Inch (tpi): 20 1st end **Maximum Operating Pressure:** 3000.0 pounds per square inch single response **Thread Size:** 0.438 inches 1st end Seat Angle: 37.0 degrees all ends **Outside Diameter Tube Accommodated:** 0.250 inches 1st end Material:

Stainless steel body

Media For Which Designed:
Air single response

Surface Treatment:
Passivate

Style Designator:
Straight thru

Thread Series Designator:
Unf all ends

NSN 4820-00-832-9646

Lift-check Valve - Page 2 of 2



		ife:	

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A530b0