NSN 4820-00-832-9736

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-832-9736

Thread Class:
3a 1st end
Thread Direction:
Right-hand 1st end
Flow Control Device:
Poppet
Bonnet Type:
Packing retaining
Disk Loading Method:
Spring
Maximum Operating Temp:
400.0 degrees fahrenheit single response
Connection Style:
G50 external seat for gasket seal (boss) 1st end
Valve Operation Method:
Automatic
Connection Type:
Threaded external boss 1st end
Features Provided:
Pressure tight outlet side
Thready Qty Per Inch (tpi):
20 1st end
Adjustable Pressure Range:
+60.0/+150.0 pounds per square inch
Maximum Operating Pressure:
150.0 pounds per square inch single response
Thread Size:
0.437 inches 1st end
Opening Pressure Setting:
125.0 pounds per square inch
Outside Diameter Tube Accommodated:
0.250 inches 1st end
Material:
Aluminum alloy 2024 body
Material Specification:
Qq-a-225/8, alloy6061, t6 federal specification single material response flow control device
Media For Which Designed:
Oxygen, gaseous 4th response
Style Designator:
Err-090
Thread Series Designator:
Haf 4-4 and

Unf 1st end

NSN 4820-00-832-9736

Safety Relief Valve - Page 2 of 2



_					
•	n	0 1	•	12	e:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A046b0