## NSN 4820-00-835-3873

Safety Relief Valve - Page 1 of 2

Flow Control Device:

**Disk Loading Method:** 

**Bolt Hole Quantity:** 

**End Application:** 

**Maximum Operating Temp:** 

**Valve Operation Method:** 

150.0 degrees fahrenheit single response

Combat system support equipment

Disk

Spring

6 1st end

Automatic



View Online at https://aerobasegroup.com/nsn/4820-00-835-3873

Flange Shape:
Round with holes 1st end
Connection Type:
Flange 1st end
Adjustable Pressure Range:
+400.0/+499.0 pounds per square inch
Maximum Operating Pressure:
400.0 pounds per square inch single response
Outside Diameter:
6.125 inches 1st end
Thickness:
0.500 inches 1st end
Bolt Hole Diameter:
0.562 inches 1st end
Bolt Circle Diameter:
5.000 inches 1st end
Flange Face Design:
Plain 1st end
Special Features:
Valve sz 2.500 in.
Material:
Copper alloy body
Media For Which Designed:
Water, salt single response
Style Designator:
Err-090
Reference Number Differentiating Characteristics:
As differentiated by mfg specification type a2, class c, this valveequipped with gag assembly
Shelf Life:
N/a

## NSN 4820-00-835-3873

Safety Relief Valve - Page 2 of 2



		• •			
ш	ın	10	<i>(</i> )+	Measure:	

--

Demilitarization:

No

Fiig:

A046b0