## NSN 4820-00-835-3873

Safety Relief Valve - Page 1 of 2

Flow Control Device:

**Disk Loading Method:** 

**Bolt Hole Quantity:** 

**End Application:** 

**Maximum Operating Temp:** 

**Valve Operation Method:** 

150.0 degrees fahrenheit single response

Combat system support equipment

Disk

Spring

6 1st end

Automatic



View Online at https://aerobasegroup.com/nsn/4820-00-835-3873

| Flange Shape:   |
|---|
| Round with holes 1st end  |
| Connection Type:  |
| Flange 1st end  |
| Adjustable Pressure Range:  |
| +400.0/+499.0 pounds per square inch  |
| Maximum Operating Pressure:   |
| 400.0 pounds per square inch single response  |
| Outside Diameter:   |
| 6.125 inches 1st end  |
| Thickness:  |
| 0.500 inches 1st end  |
| Bolt Hole Diameter:   |
| 0.562 inches 1st end  |
| Bolt Circle Diameter:   |
| 5.000 inches 1st end  |
| Flange Face Design:   |
| Plain 1st end   |
| Special Features:   |
| Valve sz 2.500 in.  |
| Material:   |
| Copper alloy body   |
| Media For Which Designed:   |
| Water, salt single response   |
| Style Designator:   |
| Err-090   |
| Reference Number Differentiating Characteristics:   |
| As differentiated by mfg specification type a2, class c, this valveequipped with gag assembly |
| Shelf Life:   |
| N/a   |
|   |
|   |
|   |

## NSN 4820-00-835-3873

Safety Relief Valve - Page 2 of 2



|   |    | • • |             |          |  |
|---|----|-----|-------------|----------|--|
| ш | ın | 10  | <i>(</i> )+ | Measure: |  |
|   |    |     |             |          |  |

--

Demilitarization:

No

Fiig:

A046b0